

Hybrid process enhances BNR without added reactor volume

The ActiveCell® Integrated Fixed-film Activated Sludge (IFAS) process helps treatment plants remove more nutrients from wastewater before discharge. Afnan Din of Headworks BIO Inc. explains.

One of the major concerns regarding municipal wastewater treatment plant discharge is the rising concentration of nutrient compounds, specifically nitrogen and phosphorus. The ActiveCell® process, developed by the US company Headworks BIO Inc., enables existing plants to solve this problem by enhancing biological nutrient removal (BNR) without adding reactor volume. BNR is a process used to remove nitrogen and phosphorus from the wastewater before it is discharged into surface or ground water.

Nitrogen and phosphorus are the primary causes of cultural eutrophication (i.e., nutrient enrichment due to human activities) in surface waters. The most recognizable manifestations of this eutrophication are algal blooms that occur during the summer. Chronic symptoms of over-enrichment include low dissolved oxygen, fish kills, murky water, and depletion of desirable flora and fauna.

Wastewater treatment plants that employ conventional biological treatment processes designed to meet secondary treatment effluent standards typically do not remove total nitrogen (TN) or total phosphorus (TP) to the extent needed to protect receiving waters. However, wastewater treatment facilities are increasingly being required to address this issue by

implementing treatment processes that reduce effluent nutrient concentrations to levels that regulators deem sufficient to protect the environment.

Implementation usually involves major process modifications to a plant, such as making a portion of the aeration basin anaerobic and/or anoxic. This reduces the aerobic volume and limits nitrification capacity. Clarifier solids loading is usually the factor that limits the concentration of biomass available for nitrification; therefore, common practice is to increase bioreactor volume in order to increase treatment capacity. This can be very expensive and sometimes impossible if space is limited.

ActiveCell® solution

The ActiveCell process employs the benefits of fixed-film systems into the suspended growth-activated sludge process. This hybrid process is referred to as Integrated Fixed-film Activated Sludge (IFAS) technology.

The ActiveCell IFAS process is typically divided into a series of stages, including anaerobic, anoxic, and aerobic volumes in such a way that is similar to some well-known BNR configurations. Within the ActiveCell IFAS process, media is filled in the aerobic stages and retained by stainless steel wedge-wire screens located at the effluent end of the process stage.

The IFAS process allows gradual, multi-step, plant expansion due to the progressive addition of media.

Placing ActiveCell media into activated sludge basins creates a combination of suspended and attached growth biology that optimizes the benefits of both of these systems. Each individual piece of ActiveCell media has been designed with a very high surface area-to-volume ratio to support the growth of biofilm. The surface area provided by the media creates additional active biology above and beyond the limits of the suspended activated sludge system. This can increase reactor capacity, in terms of organic loading, or support more advanced treatment of the wastewater due to longer sludge age.

The additional fixed film biomass

does not need to be settled out and returned. Therefore, it does not increase the solids loading to the secondary clarifier, a factor that often limits the treatment capacity of activated sludge systems. IFAS technology addresses the need for increasing activated sludge plant capacity without additional clarifier or aeration basin volume. The fixed biomass also contributes to the ability of the process to respond to organic or hydraulic shock loads and to recover from upsets.

The ActiveCell IFAS process is a cost-effective solution for upgrading existing plants to support BNR without adding reactor volume. Portions of existing aerobic zones can be partitioned into anaerobic or anoxic zones for advanced BNR treatment. Furthermore, the addition of ActiveCell media to the remaining aerobic zones increases the solids retention time to a level needed for nitrification.

The team of process design experts at Headworks BIO employs advanced modeling and design tools to determine the size, location, and quantity of ActiveCell media for each stage of the process to achieve the desired level of nutrient removal.

IFAS technology advantages

IFAS provides a stable process. Due to attached growth, toxic upsets and hydraulic “wash out” events affect only the top layers of the biofilm containing the microbial population, so process recovery is fast and smooth. It enables quantitative nitrification of the activated sludge, even at a low sludge age, by maintaining a separate population on the media. A biofilm rich with autotrophs allows stable nitrification even at low temperatures. Nitrification in the IFAS system occurs at low suspended sludge age, resulting in better sludge settling properties.

Author's Note

Afnan Din is the vice president and process manager for the Middle East and North Africa region for Headworks BIO Inc., based in Houston, Texas, USA.

